

# Trust our certified installers



Entrusting your comfort to Fujitsu is ensuring cozy comfort all year, maximum performance when you really need it and substantial energy savings.

It is also assurance of a flawless installation guaranteeing optimal system performance because each Fujitsu system is installed by a licensed dealer who has received a specific technical training and has all the skills required to recommend the unit best suited to your needs and comfort standards. His recommendation will be based not only on the living space, but also on insulation, windows, number of occupants and your lifestyle and habits.

## Standard features

- Wireless remote control
- Apple catechin filter
- Ion deodorizing filter
- Sleep timer
- 24 hour timer
- Weekly timer
- Dry mode
- Auto louver: 4-way
- Auto mode
- Powerful operation mode
- Minimum heat (50°F/10°C)
- Auto restart/reset
- Auto changeover
- Low ambient cooling
- Cold prevention
- Remote temp. sensor\*
- Economy mode
- Energy saving program
- Quiet mode (indoor)
- Low noise mode
- 3<sup>rd</sup> party device control†



- Low ambient cooling
- Cold prevention
- Remote temp. sensor\*
- Economy mode
- Energy saving program
- Quiet mode (indoor)
- Low noise mode
- 3<sup>rd</sup> party device control†

Design wireless remote control

\*Remote temperature sensor is available for the 9RLS3H and 12RLS3H models only.  
 †3<sup>rd</sup> party device control is available for the 9RLS3H and 12RLS3H models only.

## Optional accessories

- Wired remote controller: UTY-RVNUM, backlit and includes room temperature
- PEB1W or PEB1B Pebble Wi-Fi controller

### Other XLTH products

XLTH Full Inverter Series models and their accessories are available for the following models:

	9RLS3H	12RLS3H	15RLS3H	18RLXFWH	24RLXFWH	30RLXEH
Min. - max. cooling BTU/h	3,100 - 12,000	3,100 - 13,600	3,100 - 18,400	7,000 - 23,000	9,900 - 27,300	9,900 - 32,400
Min. - max. heating BTU/h	3,100 - 22,000	3,100 - 22,100	3,100 - 23,900	7,000 - 29,000	7,500 - 36,200	8,000 - 37,500
SEER BTU/hW	33.0	29.3	25.3	20.0	19.5	18.7
HSPF BTU/hW	14.0	13.8	13.3	10.4	10.5	11.7
EER clg./htg BTU/hW	18.0	15.2	13.9	13.3	12.5	12.5
Cooling operating range °F (°C)	14 to 115 (-10 to 46)	14 to 115 (-10 to 46)	14 to 115 (-10 to 46)	-5 to 115 (-20 to 46)	-5 to 115 (-20 to 46)	-5 to 115 (-20 to 46)
Heating operating range °F (°C)	-15 to 75 (-26 to 24)	-15 to 75 (-26 to 24)	-15 to 75 (-26 to 24)	-15 to 75 (-26 to 24)	-15 to 75 (-26 to 24)	-15 to 75 (-26 to 24)
Moisture removal pt./h (l/h)	2.6 (1.2)	2.7 (1.3)	4.0 (1.9)	5.9 (2.8)	6.3 (3.0)	9.7 (4.6)
Voltage/frequency/phase	208 - 230/60/1	208 - 230/60/1	208 - 230/60/1	208 - 230/60/1	208 - 230/60/1	208-230/60/1
Max. Cr. Bkr (A)	15	15	20	20	20	30
Air circ. C.F.M. (m <sup>3</sup> /h): Hi	489 (830)	489 (830)	547 (930)	541 (920)	Clg 659 (1,120) Htg 677 (1,150)	812 (1,380)
Medium	400 (680)	400 (680)	459 (780)	435 (740)	530 (900)	665 (1,130)
Low	341 (580)	341 (580)	371 (630)	365 (620)	435 (740)	536 (910)
Quiet	224 (380)	224 (380)	Clg 259 (440) Htg 294 (500)	Clg 306 (520) Htg 318 (540)	365 (620)	418 (710)
Noise level clg./htg dB(A): Hi	42/41	42/41	45/45	43/44	49/49	50/49
Medium	37/35	37/35	40/39	37/37	42/42	45/44
Low	32/31	32/31	34/33	33/33	37/37	38/38
Quiet	23/23	23/23	26/27	28/28	33/33	32/32
Outdoor noise level clg./htg dB(A)	42/47	43/47	49/50	47/50	54/55	53/54
Fan speeds, stage	4 + auto	4 + auto	4 + auto	4 + auto	4 + auto	4 + auto
Air direction: Horizontal	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Vertical	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Air filter	Washable	Washable	Washable	Washable	Washable	Washable
Combined min. lgth ft (m)	10 (3)	10 (3)	10 (3)	16 (5)	16 (5)	16 (5)
Combined max. lgth ft (m)	66 (20)	66 (20)	66 (20)	164 (50)	164 (50)	246 (75)
Max. vertical diff. ft (m)	49 (15)	49 (15)	49 (15)	98 (30)	98 (30)	98 (30)
Conn. pipe diameter in	Suc. 3/8 Dis. 1/4	Suc. 3/8 Dis. 1/4	Suc. 1/2 Dis. 1/4	Suc. 3/8 Dis. 5/8	Suc. 3/8 Dis. 5/8	Suc. 3/8 Dis. 5/8
Net weight lbs (kg)	31 (14) 86 (39)	31 (14) 86 (39)	31 (14) 88 (40)	31 (14) 135 (61)	31 (14) 135 (61)	40 (18) 205 (93)
Dimensions: Height in (mm)	11 5/8 (295) 24 7/16 (620)	11 5/8 (295) 24 7/16 (620)	11 5/8 (295) 24 7/16 (620)	12 5/8 (320) 32 3/4 (830)	12 5/8 (320) 32 3/4 (830)	13 3/8 (340) 50 (1,290) 13 1/6 (330)
Width in (mm)	37 (940) 31 1/8 (790)	37 (940) 31 1/8 (790)	37 (940) 31 1/8 (790)	39 1/4 (998) 35 3/8 (900)	39 1/4 (998) 35 3/8 (900)	45 1/4 (1,150) 35 3/8 (900)
Depth in (mm)	10 5/8 (270) 11 7/16 (290)	10 5/8 (270) 11 7/16 (290)	10 5/8 (270) 11 7/16 (290)	9 (228) 13 (330)	9 (228) 13 (330)	11 (280) 13 (330)

- ASU9RLS indoor
- AOU9RLS3H outdoor
- ASU12RLS indoor
- AOU12RLS3H outdoor
- ASU15RLS indoor
- AOU15RLS3H outdoor
- ASU18RLF indoor
- AOU18RLF-FWH outdoor
- ASU24RLF indoor
- AOU24RLF-FWH outdoor
- ASU30RLE indoor
- AOU30RLXEH outdoor



Authorized dealer

Fujitsu is a registered trademark of Fujitsu Ltd. All other trademarks are the property of their respective owners. © 2014 Fujitsu Ltd. All rights reserved. FUJITSU is a registered trademark of Fujitsu Ltd. All other trademarks are the property of their respective owners.

